



THREE SINHA

TURNSTILE SYSTEM



SLB301



SWB102



TTS351L



FLB142



SWB301



TTS311



SWB302



FLB141



SLB302

NORMAL SPEED SWING BARRIER

1. Chassis Material: Domestic (304#) Stainless Steel
2. Swing arm length: 500-800mm
3. Weight: 80Kg
4. Swing arm transmission angle: 180 degrees
5. Swing direction: one-way or two-way
6. Working Voltage: A6220 + 10% V 50 + 10% HZ
7. Driving motor: DC brush motor (24V)
8. Input Interface: Dry Contact Signal or 12V Level Signal or 12V Pulse Signal with Pulse Width (>100ms), Driving Current (> 10mA)
9. Communication Interface: RS485 Standard Distance < 1200m
10. LED indicator: 1 card reading window; 2
11. Speed: 40 people per minute (usually open), 25-30 people per minute (usually closed)
12. Opening and closing time of gate: 1-2 seconds
13. The time required to enter the traffic state after power-on: 3 seconds
14. Automatic reset time after failure: 10 seconds
15. Working environment: indoor and outdoor (shade)
16. Temperature: -10°C - 50°C Relative Humidity: < 90%

FAST SPEED SWING BARRIER

1. 1400 Length * 200 Width * 1000 Height
2. Power supply voltage: A6220 + 10% V, 50HZ
3. Working environment: Indoor and outdoor (optional)
4. Working environment temperature: - 15 - 60
5. Channel Width: 600-750MM, Standard Channel: 750
6. Input interface: 12V Level Signal or Pulse Width
7. Outward Size: 1400 Length * 200 Width * 1000 Height
8. Alarm mode: voice prompt and alarm flicker are optional
9. Box Material: National Standard 304 Stainless Steel
10. Thickness: Non-standard 2.0mm for case cover and other non-standard 1.5mm
11. Gate material: toughened glass plexiglass acrylic board [Optional]
12. Technological Standard: Laser Cutting Process, Beautiful Appearance
12. Driving motor: brush motor 13. Core Voltage: DC24V
14. Control signal: switching signal
15. Speed: about 35-40 person - most minutes.
16. Reader mounting position: 2 pcs
17. Opening and closing time of gate: about 0.4 - 0.5 seconds

TRIPOD TURNSTILE

- Material: 304# stainless steel material.
1. Thickness : 1.2mm thickness
 2. Size : 980mm*420mm*330*510mm
 3. Control : IC/ID card & Manual Operation
 4. (Can support access control system)

NEGOMBO SHOWROOM
32, Colombo Road, Kuruna, Katunayaka.
Hotline: 0317 65 65 65 Mobile: 0768 768 155
Email: negombo@threesinha.lk

MATARA SHOWROOM
769, Galle Road, Madaha, Walagama, Matara.
Hotline: 0317 65 65 65 Mobile: 0768 768 155
Email: matara@threesinha.lk

KANDY SHOWROOM
302, William Gopallawa Mawatha, Kandy.
Hotline: 0817 65 65 65 Mobile: 0768 768 155
Email: kandy@threesinha.lk

www.threesinha.lk



THREE SINHA INDUSTRIES (PVT) LTD

Head Office: 448, Nawala Road, Koswatta, Rajagiriya.
Hotline: 0117 65 65 65 Email: marketing@threesinha.lk



www.threesinha.lk

Kandy Branch: 0817 65 65 65

Matara Branch: 0417 65 65 65

Negombo Branch: 0317 65 65 65