



# THREE SINHA

# TURNSTILE SYSTEM



SLB301

TTS311



SWB102



TTS351L



FLB142



SWB301



SWB302



FLB141



SLB302

## NORMAL SPEED SWING BARRIER

- 1.Chassis Material : Domestic(304#)Stainless Steel.
- 2.Swing arm length : 500-800mm
- 3.Weight :80Kg
- 4.Swing arm transmission angle:180degrees
- 5.Swing direction : one-way- or two-way
- 6.Working Voltage :A6220+10%V 50+10%HZ
- 7.Driving motor : DC brush motor(24V)
- 8.Input Interface: Dry Contact Signal or 12V Level Singnal or 12V Pules Signal with Pules Width (>100ms), Driving Current (>10mA)
- 9.Communication Interface:RS485 Standed Distance<1200m.
- 10.LED Indicator: 1card reading window :2
- 11.Speed :40 people per minute (usually open),25-30 people per minute (usually closed)
- 12.Opening and closing time of gate : 1-2 seconds
- 13.The time required to enter the traffic state after power - on : 03 seconds
- 14.Automatic reset time after failure :10 seconds
- 15.Working environment : indoor and outdoor.(shade)
- 16.Temperature - 10 °C - 50°C Relative Humidity : <90%

## FAST SPEED SWING BARRIER

- 1.1400 Length\* 200 Width\*1000 Height
- 2.Power supply voltage:A6220+10%V,50HZ
- 3.Working environment : Indoor and outdoor (Optional)
- 4.Working environment temperature:-15-60
- 5.Channel Width: 600-750MM,Standard channel:750
- 6.Input interface: 12VLevel Signal or Pulse Width
- 7.Outward Size:1400 Length\*200 Width\* 1000 Height
- 8.Alarm mode:Voice prompt & alarm flicker are optional
- 9.Box Material:National Standard 304 Stainless Steel
- 10.Thickness:Non-Standard 2.0mm for case cover and other non-standard 1.5mm
- 11.Gate material:toughened glass Plexiglas acrylic board (optional)
- 12.Technological-Standard:Laser Cutting Process, Beautiful Appearance
- 13.Driving motor:brush motor
- 14.core voltage:DC24V
- 15.Control signal: Switching signal
- 16.Speed: about 35-40 person-most minutes
- 17.Reader mounting position: 2 pcs
- 18.Opening and closing time of gate:about 0.4-0.5 seconds

## TRIPOD TURNSTILE

- Material: 304# stainless steel material.
- 1.Thickness :1.2mm thickness
  - 2.Size : 980mm\*420mm-330\*510mm
  - 3.Control : ICAD Card & Manual Operation
  - 4.(Can support access control system)

## NEGOMBO SHOWROOM

32,Colombo Road,Kurana,Katunayaka.  
Hotline: 0317 65 65 65 Mobile: 0768 768 155  
Email: negambo@threesinha.lk

## MATARA SHOWROOM

769, Galle Road,Madiha,Walagama,Matara.  
Hotline:0417 65 65 65 Mobile:0768 768 170  
Email: matara@threesinha.lk

## KANDY SHOWROOM

302, William Gopallawa Mawatha,Kandy.  
Hotline: 0817 65 65 65 Mobile: 0768 768 150  
Email: kandy@threesinha.lk



# THREE SINHA

# INDUSTRIES (PVT) LTD.



Head office: 448, Nawala Road, Koswatta, Rajagiriya.  
Hotline: 0117 65 65 65 Email: marketing@threesinha.lk

[www.threesinha.lk](http://www.threesinha.lk)

Kandy Branch: 0817 65 65 65

Matara Branch : 0417 65 65 65

Negombo Branch: 0317 65 65 65